



KONICA MINOLTA

MINIMISE ALL. MAXIMISE ALL.

bizhub

C3850 / C3350



Giving Shape to Ideas

Specifications

bizhub C3850 / C3350 General Specifications

Product name	bizhub C3850	bizhub C3350
Type	Desktop Full Colour Printer / Copier / Scanner	
Colour Support	Full-Colour	
Copy Resolution	Scan: Main: 600 dpi x Sub: 600 dpi Print: "Default mode: Main: 600 dpi x Sub: 600 dpi High Quality mode (half speed): Main: 1,200 dpi, 1,200 dpi"	
Gradation	256	
Memory Capacity (Std./Max.)	1 GB / 2 GB	
HDD	320 GB	
Original Type	Sheets, Books, Objects	
Max. Original Size	A4 or Legal (8 – 1/2" x 14")	
Output Size	Legal, Postcard, A4 to A5	
Warm-Up Time ¹	30 sec. or less	
First Copy Out Time ²	Colour: 8.1 sec. or less / 10.0 sec. or less B/W: 7.2 sec. or less / 9.0 sec. or less	
Copy Speed (A4 / Letter)	Colour: 38 ppm / 40 ppm / 33 ppm / 35 ppm B / W: 38 ppm / 40 ppm / 33 ppm / 35 ppm	
Copy Magnification	Fixed Same Magnification: "x0.250 – x4.000 Preset: x2.000, x1.631, x1.545, x1.414, x1.294, x1.224, x1.154, x1.000, x0.866, x0.816, x0.785, x0.707, x0.647, x0.607, x0.500 Variable Zoom: 25 – 400% (in 0.1% increments)	
Paper Capacity (75 g/m ²)	Tray 1: 550 sheets Multiple Bypass Tray: 100 sheets (Custom paper: 20 sheets, Envelopes: 10 sheets)	
Max. Paper Capacity (75 g/m ²)	1,650 sheets	
Paper Weight	Tray 1: 60 – 210g / m ² Multiple Bypass Tray: 60 – 210g / m ² Optional Tray: 60 – 90g / m ²	
Multiple Copy	1 – 999 sheets	
Auto Duplex	Paper Size: B5S to Legal Paper Weight: 60 to 210 g / m ²	
Power Requirements	AC220 to 240 V 7.5A (50 to 60 Hz) AC110 to 127 V 12.0A (50 to 60 Hz)	
Max. Power Consumption	1,700W / 220-240V 1,550W / 110-127V	
Dimensions [W] x [D] x [H]	555 x 584 x 603 mm	
Weight (Main Unit + ADF)	47.6 kg (with consumables) / 47.5 kg (with consumables) / 46.3 kg (without toner bottles) / 46.2 kg (without toner bottles)	
Space Requirements [W] x [D] x [H]	809 x 932 x 829 mm	

- 1 Warm-up time may vary depending on the operating environment and usage. The time required to start printing when both the main power and sub-power switches are turned from OFF to ON. (23°C, std. voltage)
- 2 A4 full size/using the first tray/scanning from the original glass surface.
- 3 Without options, with paper trays pulled out, and multiple bypass tray and ADF opened.

Printer Specifications

Product name	bizhub C3850	bizhub C3350
Type	Embedded	
CPU	MV78 x 30 (1066MHz)	
Memory	Shared with the copier	
Print Speed	Same as Copy Speed (when using the same original)	
HDD	320 GB (Shared with the copier)	
Print Resolution	600 x 600 dpi, 1,200 x 1,200 dpi	
PDL	PCL5e/c Emulation, PCL XL Ver. 2.1 Emulation, PostScript 3 Emulation (3016), XPS Ver. 1.0	
Protocol	TCP/IP, IPX/SPX (NDS support), SMB (NetBEUI), LPD, IPP1.1, SNMP, HTTP, WSD, AppleTalk	
Support OS	Windows XP SP3 / XP SP2 64bit / Vista SP2 / Vista SP2 64-bit / 7 SP1 / 8 / Windows Server 2003 SP2 / Server 2003 SP2 64-bit / Server 2008 SP2 / Server 2008 SP2 64-bit / Mac OS X / Linux Redhat 9.0 / SUSE 10	
Fonts	PCL: 80 Roman fonts PS: 137 Roman Type1 fonts	
Interface	Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T), USB 1.1, USB 2.0, USB Host	

Scanning Specifications

Type	Full-Colour Scanner
Interface	Ethernet (10BASE-T / 100BASE-TX / 1000BASE-T)
Driver	TWAIN Driver
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV), TCP Socket WSD
Scanning Speed (A4, 300 dpi)	B&W / Colour: 35 opm
Scanning Size	Max. A4 or Legal (8 – 1/2" x 14")
Output Format	TIFF, JPEG, PDF, Compact PDF, XPS, PDF/A
Scanning Resolution	Push: 300 dpi / 600 dpi Pull: 300 dpi / 600 dpi
Main Functions	Scan to E-Mail, Scan to FTP, Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to USB

FAX KIT* FK-512 (Optional) *Fax mount kit MK-738 is required.

Communication Line	PSTN (Public switch telephone network), PBX (private branch exchange), G3 (Fax line)
Scan Line Density	G3 (8dot / mm x 3.85line / mm - 600 x 600 dpi)
Modem Speed	2.4kbps - 33.6kbps
Transmission Time	Approx. 3 sec (A4, V.34, 33.6kbps, JBIG)
Scanning Speed	Monochrome: 35 ppm (A4)
Coding	MH, MR, MMR, JBIG
Communication Mode	ECM / Super G3

Space Requirements

Dimensions (unit: mm)

